

# MSK MILD STEEL KIOSK SPECIFICATIONS

MSK kiosks are manufactured from 2mm zintec sheet steel to BS6687-1986 (chromate washed substrate BS1449-2.5 microns).

Kiosks are pressformed and welded to give excellent weather protection and good earth continuity and finished to the following paint specification:

1. Degrease and clean to remove surface dirt
2. One coat of two-pack etching primer
3. Air dry for one hour
4. Two coats of pure polyester powder paint to give a minimum dry film thickness of 50 microns
5. Stove at 180 degrees for 45 minutes

The finished colour is dark green shade RAL 6005 textured type finish.

The kiosks are fitted with the following equipment as standard:

1. Two kiosk lifting brackets
2. 14mm floor fixings
3. Door retaining stay(s) to hold door(s) open at 90 degrees
4. Flush 7mm triangular door locks
5. Full height mounting rails at the rear of each section
6. Internal hinges
7. Earthing points
8. Two air vents (one on each side)



	Height (mm)	Width	Depth	Doors
MSK 1	1250	750	400	1
MSK 2	1250	1250	400	2
MSK 3	1250	1250	400	1
MSK 4	1250	1500	400	2
MSK 5	1250	1600	400	2
MSK 6	1500	1500	500	2
MSK 7	1500	2000	500	2
MSK 8	1500	2250	500	2
MSK 9	1500	2750	500	3