

ELETTROPOMPE AUTOADESCANTI PER CARBURANTI

Self priming electric pumps for fuels

Electropompes autoamorçantes pour gas-oil

ELETTROPOMPE PER TRAVASO GASOLIO a girante aperta, guarnizioni speciali

Self priming electric pumps to transfer gas oil, open impeller, special seals

Electropompes autoamorçantes pour transvasement du gas-oil, turbine ouverte, garnitures spéciales



Cat. Cat.	Pompa Pump Pompe	HP HP CV	KW KW KW	Motore Motor Moteur	Aspirazione	Peso Weight Poids (Kg)	Dimensioni Dimensions LxLxH (mm)	H Q	Prestazioni				Prezzo Price-Prix €
					Mandata Suction Delivery				Performances Performances				
EA2L	B1KQ-A	0,75	0,55	230 M.	1"	15	216	mt	1	4	8	12	
EA2M				—	—		375	—	—	—	—	—	
EA2P	B1KQ-A	0,75	0,55	230/400 T.	1"	18	285	l/m'	120	105	76	30	
EA2R				12 Volt. C.C.	—		190	mt	2	4	8	12	
3516	B1½KQ-A	1	0,75	24 Volt. C.C.	1"	19,5	430	—	—	—	—	—	
3501				230 M.	1½"		180	mt	2	5	10	15	
EA2V	B2KQ-A	2	1,5	230/400 T.	1½"	21	300	l/m'	325	300	220	90	
EA1S				230 M.	2"		185	mt	2	6	10	15	
EA9C	B3KQ-A	3	2,2	230/400 T.	2"	30	300	l/m'	500	400	330	100	
EAM7				230 M.	3"		185	mt	5	8	12	15	
EA1A	B3XR-A	5,5	4	—	—	59	445	—	—	—	—	—	
				230/400 T.	3"		300	l/m'	700	600	400	100	
				400/690 T.	3"		280	mt	8	15	20	22	
				—	—		635	—	—	—	—	—	
				—	3"		400	l/m'	900	700	350	200	