

DIR 2

RANGE 1.5÷7.5 kW

**DIRECT ON LINE ELECTROMECHANICAL
CONTROL PANEL FOR 2 SINGLE
OR THREE PHASE MOTORS**

- INTEGRATED MODULE WITH MOTOR PROTECTION, INPUT AND OUTPUT (as standard)



Automated Environmental Systems

Sales and service 01842 819130



40cm x 30cm x 24cm (including isolator switch)

MAIN FEATURES

- Power input for 2 motors 1-230V ±10% 50/60Hz
- Power input for 2 motors 3-400V ±10% 50/60Hz
- N.2 AUTO-O-MAN selectors (stable)
- N.2 Motor running green light indicator
- "Power on" blu light indicator
- N.2 Overload red light indicator
- Main disconnect switch with door lock
- N.2 Contactors
- N.2 Thermal protection relay
- Connection terminals
- Transformer for auxiliary circuit
- Auxiliary circuit protection fuses
- Motor protection fuses
- Cable glands
- IP55 plastic enclosure (IP65 available on request)
- Ambient temperature: -5/+40 °C
- Relative humidity 50% at 40 °C (condensate free)

INTEGRATED MODULE FUNCTIONS

- Clear or waste water
- Lack of the phases control
- Min/max voltage control with delay and automatic reset
- Self holding
- Min level with probe and float switch
- Max level with float switch
- BMS (Building Management system terminals on demand)

INPUT

- N.1 x Probes level control for 2 pumps
- N.4 x Float switch/pressure switch
- N.2 x Klixon motor protection

ALARMS

- N.1 x 24V
- N.1 x NO free contact