

PELICAN 231/251/281

2" x 2" Self Priming Diaphragm Sludge Pump
with
Lombardini diesel engine, Honda petrol engine
or Single phase electric motor drive

Designed to Handle Mud, Sludge, Sewage and Other Thick Liquids that Flow



- Cast Aluminium for Portability and Durability
- Thermoplastic Rubber Diaphragm and Polyurethane Flap Valves
- Solids Handling up to 40 mm
- Continuous Dry Running without Damage
- Self Priming to 7.5 m
- Screwed BSP Male Connections
- Easy Cleanout & Maintenance
- Mounted on 2 Wheel Site Trolley
- Many Options Including – Spares Kits – Hoses – Suction Lance for Pit Latrines - Quick Couplings – Case Packing

Special Feature: Base of pump can be rotated through 90° for access through doors etc.

Powered by either a Lombardini lightweight industrial air cooled single cylinder diesel engine, a Honda GX120 petrol engine or a single phase (230v) electric motor. These pumps are the ideal solution to many pumping and dewatering applications. Sets are supplied with Pump and Engine Operating and Instruction Manuals.

Model	size	Prime mover	Max flow l/m	Max head m	Solids mm	L x W x H cm	Weight
Pelican 281	2"	230v electric	120	10(7.5)*	40	100 x 65 x 59	60 kg
Pelican 231	2"	Honda petrol	190	10 (7.5)*	40	100 x 65 x 59	57kg
Pelican 251	2"	Lombardini 15LD225	190	10 (7.5)*	40	100 x 65 x 59	72 kg

*Recommended maximum for continuous running